



Active Unlocking with Graphite (S158)

Unlocking spray that acts with the properties of graphite. This spray is ideal for professional uses, for example by mechanicals, auto electricians and autobody repairman.



Quantity	400 ml
Barcode	EAN 13: 8034108892337
Box / Case	12 pz

ACTIVE UNBLOCKING WITH GRAPHITE – This is a technical professional product with high penetrating power. It reaches deep into the layers of rust, dry grease, coal deposits and metal powder, canceling cohesion. The micro particles of lamellar graphite penetrating into small areas are resistant to high temperatures and extreme loading conditions. It allows the unblocking action even when the oil-fat phase has been degraded by the combustion of the heat generated by the friction. It unlocks rusted bolts, fittings, valves, car mufflers, flanges, threaded rods, pistons, chains etc..

Technical Specifications:

Aspect	Tin-Plate can containing under pressure fluid
Color	Light brown-grey
Odour	Characteristic of solvent
Relative density	at 20°C 0,68 ÷ 0,71 g/ml
Flash point	Und.0° C extremely flammable
Pressure at 20°C	4/6 bar
Freezing point	< -66°C (liquid base)
Boiling point	176°C circa (liquid base)
Flash point	40 °C ((liquid base)
Vapor tension	> 5 bar (20°C)
Viscosity	< 3 cSt - 15 cSt 40°C (oily base)
Solubility	Insoluble in water
Operating time	-60°C / +220 °C c.a.

HOW TO USE: Shake well before use. Spray the product on the part to treated, leave for a few minutes, in the case of rusted parts proceed with the unlocking. In presence of more resistant deposits repeat the operation. The product can be also be sprayed with the straw attached to the cap. **PRECAUTIONS:** Do not apply to equipment in tension. Do not apply to materials overheated.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT