



Traffic Marker Paint 750 ml (V405)

This is a professional product, create your parking or safety lines in your warehouse! This spray makes visible lines for any different works and construction site too!

TRAFFIC MARKER - Ideal for creating general parking signs and signaling danger zones. To make visible the terms of reference such as siting, excavation, demarcation of maintenance works. It is resistant to weathering and chemicals. It can be used on numerous surfaces such as cement, asphalt, glass, wood, synthetic materials. Lines of high precision can be made with this product. The width of the line can vary from 4 to 6 inches depending on the setting. The length varies depending on the traveling speed and the porosity of the surface: 40-50 m.



HOW TO USE: clean the surface thoroughly to treat, open the cap, shake the bottle vigorously for 1 minute, until you hear the internal balls move freely. It is an high viscosity product, so is better occasionally shake the can also during use. The spray can must be used upside down. The spray can could be used with specific car road "striper" or manually. **Manual use:** Press the nozzle and turn upside down the can, the width of the lines can change depending of the distance spraying (10 ÷ 20 cm).

Technical Specifications:

Quantity	750 ml
Box / Case	12 Pz.
Aspect	Tin-plate can containing under pressure fluid
Colour	Yellow, Blue, White
Odour	Typical of solvent
Relative density	At 20°C 0,90 ÷ 0,94 g/ml
Flash point	< 0° C extremely flammable
Viscosity Ford Cup	From 20 to 26"
Dry residual in the can	From 40% to 45%
Pressure	at 20°C 5,5 ± 1, bar
Brillance-gloss	From 10 to 15 gloss
Operating temperature	-10°C/+100°C(peaks 150°C)
Drying times	Out of dust 10 minutes
	Dry on touch 15 minutes
	Dry on depth 45 minutes
Color cap in reference tint.	
Fields of application: Concrete, asphalt, cement surfaces in general.	
Product subject to Directive C.O.V. Subcategory: Finishing Special Value Limit VOC: 840 g / liter max actual content: 640 g / liter	
Product connected to the signal road car Cod. CAR.	

Use with signal road car: insert the bottle with the dispenser inserted into the slot. When the work is finished, the valve should be cleaned by placing the dispensing bottle vertically until the spill the propellant gas only. It 'also necessary to clean the dispenser by immersing it for a few minutes in acetone. Traces of residual paint on the dispenser may alter the width and the definition the tracing.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 5°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT